


平歯車

歯の大きさ モジュール1



ご注文の際は形式でご用命ください。


●平歯車のご注文表記例

HM 1 B 15
形式

(単位:mm)

| 形式 | 歯幅 t | 歯数 T | 歯先円直径 Do | 基準円直径 Dp | 軸穴径 d | ボス径 BD | 全長 BL | 概略重量 kg | |
|--------|---------|---------|-------------|-------------|----------|-----------|----------|------------|------|
| HM1B15 | 10 | 15 | 17.0 | 15.0 | 8 | 17.0 | 30 | 0.03 | |
| HM1B16 | | 16 | 18.0 | 16.0 | 8 | 18.0 | | 0.04 | |
| HM1B17 | | 17 | 19.0 | 17.0 | 8 | 19.0 | | 0.05 | |
| HM1B18 | | 18 | 20.0 | 18.0 | 8 | 20.0 | | 0.05 | |
| HM1B19 | | 19 | 21.0 | 19.0 | 8 | 21.0 | | 0.06 | |
| HM1B20 | | 20 | 22.0 | 20.0 | 8 | 16.0 | | 20 | 0.03 |
| HM1B21 | | 21 | 23.0 | 21.0 | 8 | 17.0 | 0.03 | | |
| HM1B22 | | 22 | 24.0 | 22.0 | 8 | 18.0 | 0.04 | | |
| HM1B23 | | 23 | 25.0 | 23.0 | 8 | 18.0 | 0.04 | | |
| HM1B24 | | 24 | 26.0 | 24.0 | 8 | 20.0 | 0.05 | | |
| HM1B25 | | 25 | 27.0 | 25.0 | 8 | 20.0 | 0.05 | | |
| HM1B26 | | 26 | 28.0 | 26.0 | 8 | 22.0 | 0.06 | | |
| HM1B27 | | 27 | 29.0 | 27.0 | 8 | 22.0 | 0.06 | | |
| HM1B28 | | 28 | 30.0 | 28.0 | 8 | 22.0 | 0.07 | | |
| HM1B29 | | 29 | 31.0 | 29.0 | 8 | 24.0 | 0.08 | | |
| HM1B30 | | 30 | 32.0 | 30.0 | 10 | 25.0 | 20 | | 0.08 |
| HM1B32 | | 32 | 34.0 | 32.0 | 10 | 26.0 | | | 0.10 |
| HM1B34 | | 34 | 36.0 | 34.0 | 10 | 26.0 | | | 0.11 |
| HM1B35 | | 35 | 37.0 | 35.0 | 10 | 26.0 | | | 0.11 |
| HM1B36 | | 36 | 38.0 | 36.0 | 10 | 28.0 | | 0.12 | |
| HM1B38 | | 38 | 40.0 | 38.0 | 10 | 32.0 | | 0.14 | |
| HM1B40 | | 40 | 42.0 | 40.0 | 10 | 35.0 | | 0.16 | |
| HM1B42 | | 42 | 44.0 | 42.0 | 10 | 35.0 | | 0.17 | |
| HM1B44 | | 44 | 46.0 | 44.0 | 10 | 44.0 | | 0.18 | |
| HM1B45 | | 45 | 47.0 | 45.0 | 10 | 35.0 | | 0.18 | |
| HM1B46 | | 46 | 48.0 | 46.0 | 10 | 35.0 | 0.19 | | |
| HM1B48 | | 48 | 50.0 | 48.0 | 10 | 35.0 | 0.20 | | |
| HM1B50 | | 50 | 52.0 | 50.0 | 10 | 35.0 | 0.22 | | |

●材質は機械構造用炭素鋼です。



ご注文の際は形式でご用命ください。

●平歯車のご注文表記例


HM 1.5 B 12

形式

(単位:mm)

| 形式 | 歯幅 t | 歯数 T | 歯先円直径 Do | 基準円直径 Dp | 軸穴径 d | ボス径 BD | 全長 BL | 概略重量 kg |
|----------|---------|---------|-------------|-------------|----------|-----------|----------|------------|
| HM1.5B12 | 15 | 12 | 21.0 | 18.0 | 8 | 21.0 | 30 | 0.05 |
| HM1.5B13 | | 13 | 22.5 | 19.5 | 8 | 22.5 | | 0.07 |
| HM1.5B14 | | 14 | 24.0 | 21.0 | 8 | 16.0 | | 0.06 |
| HM1.5B15 | | 15 | 25.5 | 22.5 | 8 | 18.0 | | 0.06 |
| HM1.5B16 | | 16 | 27.0 | 24.0 | 8 | 20.0 | | 0.07 |
| HM1.5B17 | | 17 | 28.5 | 25.5 | 8 | 21.0 | | 0.09 |
| HM1.5B18 | | 18 | 30.0 | 27.0 | 8 | 22.0 | | 0.09 |
| HM1.5B19 | | 19 | 31.5 | 28.5 | 8 | 23.0 | | 0.11 |
| HM1.5B20 | | 20 | 33.0 | 30.0 | 8 | 24.0 | | 0.12 |
| HM1.5B21 | | 21 | 34.5 | 31.5 | 8 | 25.0 | | 0.13 |
| HM1.5B22 | | 22 | 36.0 | 33.0 | 8 | 26.0 | | 0.15 |
| HM1.5B23 | | 23 | 37.5 | 34.5 | 8 | 27.0 | | 0.18 |
| HM1.5B24 | | 24 | 39.0 | 36.0 | 8 | 28.0 | 0.19 | |
| HM1.5B25 | | 25 | 40.5 | 37.5 | 8 | 30.0 | 0.20 | |
| HM1.5B26 | | 26 | 42.0 | 39.0 | 10 | 32.0 | 0.21 | |
| HM1.5B27 | | 27 | 43.5 | 40.5 | 10 | 34.0 | 0.23 | |
| HM1.5B28 | | 28 | 45.0 | 42.0 | 10 | 36.0 | 0.24 | |
| HM1.5B29 | | 29 | 46.5 | 43.5 | 10 | 37.0 | 0.25 | |
| HM1.5B30 | | 30 | 48.0 | 45.0 | 10 | 38.0 | 0.26 | |
| HM1.5B32 | | 32 | 51.0 | 48.0 | 10 | 40.0 | 0.30 | |
| HM1.5B34 | | 34 | 54.0 | 51.0 | 10 | 40.0 | 0.33 | |
| HM1.5B35 | | 35 | 55.5 | 52.5 | 10 | 42.0 | 0.34 | |
| HM1.5B36 | | 36 | 57.0 | 54.0 | 10 | 45.0 | 0.39 | |
| HM1.5B38 | | 38 | 60.0 | 57.0 | 12 | 45.0 | 0.43 | |
| HM1.5B40 | | 40 | 63.0 | 60.0 | 12 | 45.0 | 0.44 | |
| HM1.5B42 | | 42 | 66.0 | 63.0 | 12 | 45.0 | 0.47 | |
| HM1.5B44 | | 44 | 69.0 | 66.0 | 12 | 45.0 | 0.51 | |
| HM1.5B45 | | 45 | 70.5 | 67.5 | 12 | 45.0 | 0.52 | |
| HM1.5B46 | | 46 | 72.0 | 69.0 | 12 | 45.0 | 0.57 | |
| HM1.5B48 | | 48 | 75.0 | 72.0 | 12 | 45.0 | 0.58 | |
| HM1.5B50 | 50 | 78.0 | 75.0 | 12 | 45.0 | 0.62 | | |

●材質は機械構造用炭素鋼です。



ご注文の際は形式でご用命ください。

●平歯車のご注文表記例


HM 2 B 12

形式

(単位:mm)

| 形式 | 歯幅 t | 歯数 T | 歯先円直径 Do | 基準円直径 Dp | 軸穴径 d | ボス径 BD | 全長 BL | 概略重量 kg |
|--------|---------|---------|-------------|-------------|----------|-----------|----------|------------|
| HM2B12 | 20 | 12 | 28.0 | 24.0 | 10 | 18.0 | 30 | 0.09 |
| HM2B13 | | 13 | 30.0 | 26.0 | 10 | 20.0 | | 0.10 |
| HM2B14 | | 14 | 32.0 | 28.0 | 10 | 20.0 | | 0.10 |
| HM2B15 | | 15 | 34.0 | 30.0 | 12 | 24.0 | | 0.11 |
| HM2B16 | | 16 | 36.0 | 32.0 | 12 | 26.0 | | 0.15 |
| HM2B17 | | 17 | 38.0 | 34.0 | 12 | 28.0 | | 0.18 |
| HM2B18 | | 18 | 40.0 | 36.0 | 12 | 30.0 | | 0.20 |
| HM2B19 | | 19 | 42.0 | 38.0 | 12 | 31.0 | | 0.22 |
| HM2B20 | | 20 | 44.0 | 40.0 | 12 | 32.0 | | 0.22 |
| HM2B21 | | 21 | 46.0 | 42.0 | 12 | 34.0 | | 0.28 |
| HM2B22 | | 22 | 48.0 | 44.0 | 12 | 36.0 | | 0.30 |
| HM2B23 | | 23 | 50.0 | 46.0 | 12 | 37.0 | | 0.32 |
| HM2B24 | | 24 | 52.0 | 48.0 | 12 | 38.0 | | 0.35 |
| HM2B25 | | 25 | 54.0 | 50.0 | 12 | 40.0 | | 0.40 |
| HM2B26 | | 26 | 56.0 | 52.0 | 12 | 42.0 | | 0.42 |
| HM2B27 | | 27 | 58.0 | 54.0 | 12 | 45.0 | | 0.47 |
| HM2B28 | | 28 | 60.0 | 56.0 | 12 | 45.0 | | 0.50 |
| HM2B29 | | 29 | 62.0 | 58.0 | 12 | 47.0 | | 0.58 |
| HM2B30 | | 30 | 64.0 | 60.0 | 12 | 50.0 | | 0.58 |
| HM2B32 | | 32 | 68.0 | 64.0 | 12 | 50.0 | | 0.64 |
| HM2B34 | 34 | 72.0 | 68.0 | 12 | 50.0 | 0.74 | | |
| HM2B35 | 35 | 74.0 | 70.0 | 12 | 52.0 | 0.75 | | |
| HM2B36 | 36 | 76.0 | 72.0 | 12 | 55.0 | 0.80 | | |
| HM2B38 | 38 | 80.0 | 76.0 | 12 | 55.0 | 0.90 | | |
| HM2B40 | 40 | 84.0 | 80.0 | 15 | 55.0 | 0.93 | | |
| HM2B42 | 42 | 88.0 | 84.0 | 15 | 55.0 | 1.00 | | |
| HM2B44 | 44 | 92.0 | 88.0 | 15 | 55.0 | 1.10 | | |
| HM2B45 | 45 | 94.0 | 90.0 | 15 | 55.0 | 1.10 | | |
| HM2B46 | 46 | 96.0 | 92.0 | 15 | 55.0 | 1.20 | | |
| HM2B48 | 48 | 100.0 | 96.0 | 15 | 55.0 | 1.30 | | |
| HM2B50 | 50 | 104.0 | 100.0 | 15 | 55.0 | 1.40 | | |

●材質は機械構造用炭素鋼です。



ご注文の際は形式でご用命ください。

●平歯車のご注文表記例


HM 2.5 B 12

形式

(単位:mm)

| 形式 | 歯幅 t | 歯数 T | 歯先円直径 Do | 基準円直径 Dp | 軸穴径 d | ボス径 BD | 全長 BL | 概略重量 kg |
|----------|---------|---------|-------------|-------------|----------|-----------|----------|------------|
| HM2.5B12 | 25 | 12 | 35.0 | 30.0 | 12 | 23.0 | 37 | 0.14 |
| HM2.5B13 | | 13 | 37.5 | 32.5 | 12 | 25.0 | | 0.17 |
| HM2.5B14 | | 14 | 40.0 | 35.0 | 12 | 25.0 | | 0.20 |
| HM2.5B15 | | 15 | 42.5 | 37.5 | 15 | 30.0 | | 0.23 |
| HM2.5B16 | | 16 | 45.0 | 40.0 | 15 | 32.0 | | 0.25 |
| HM2.5B17 | | 17 | 47.5 | 42.5 | 15 | 35.0 | | 0.28 |
| HM2.5B18 | | 18 | 50.0 | 45.0 | 15 | 38.0 | | 0.35 |
| HM2.5B19 | | 19 | 52.5 | 47.5 | 15 | 39.0 | | 0.40 |
| HM2.5B20 | | 20 | 55.0 | 50.0 | 15 | 40.0 | | 0.44 |
| HM2.5B21 | | 21 | 57.5 | 52.5 | 15 | 42.0 | | 0.49 |
| HM2.5B22 | | 22 | 60.0 | 55.0 | 15 | 44.0 | | 0.53 |
| HM2.5B23 | | 23 | 62.5 | 57.5 | 15 | 46.0 | | 0.58 |
| HM2.5B24 | | 24 | 65.0 | 60.0 | 15 | 48.0 | | 0.65 |
| HM2.5B25 | | 25 | 67.5 | 62.5 | 15 | 50.0 | | 0.70 |
| HM2.5B26 | | 26 | 70.0 | 65.0 | 15 | 55.0 | | 0.83 |
| HM2.5B27 | | 27 | 72.5 | 67.5 | 15 | 60.0 | | 0.92 |
| HM2.5B28 | | 28 | 75.0 | 70.0 | 15 | 60.0 | | 1.00 |
| HM2.5B29 | | 29 | 77.5 | 72.5 | 15 | 62.0 | | 1.10 |
| HM2.5B30 | | 30 | 80.0 | 75.0 | 15 | 65.0 | | 1.20 |
| HM2.5B32 | | 32 | 85.0 | 80.0 | 15 | 70.0 | | 1.30 |
| HM2.5B34 | | 34 | 90.0 | 85.0 | 15 | 70.0 | | 1.40 |
| HM2.5B35 | | 35 | 92.5 | 87.5 | 15 | 70.0 | | 1.50 |
| HM2.5B36 | | 36 | 95.0 | 90.0 | 15 | 70.0 | | 1.60 |
| HM2.5B38 | | 38 | 100.0 | 95.0 | 20 | 70.0 | | 1.70 |
| HM2.5B40 | | 40 | 105.0 | 100.0 | 20 | 70.0 | | 1.80 |
| HM2.5B42 | | 42 | 110.0 | 105.0 | 20 | 70.0 | | 2.00 |
| HM2.5B44 | | 44 | 115.0 | 110.0 | 20 | 70.0 | | 2.10 |
| HM2.5B45 | | 45 | 117.5 | 112.5 | 20 | 70.0 | | 2.20 |
| HM2.5B46 | | 46 | 120.0 | 115.0 | 20 | 70.0 | | 2.30 |
| HM2.5B48 | | 48 | 125.0 | 120.0 | 20 | 70.0 | | 2.50 |
| HM2.5B50 | 50 | 130.0 | 125.0 | 20 | 70.0 | 2.70 | | |

●材質は機械構造用炭素鋼です。



ご注文の際は形式でご用命ください。

●平歯車のご注文表記例


HM 3 B 12

形式

(単位:mm)

| 形式 | 歯幅 t | 歯数 T | 歯先円直径 Do | 基準円直径 Dp | 軸穴径 d | ボス径 BD | 全長 BL | 概略重量 kg |
|--------|---------|---------|-------------|-------------|----------|-----------|----------|------------|
| HM3B12 | 30 | 12 | 42.0 | 36.0 | 15 | 28.0 | 45 | 0.25 |
| HM3B13 | | 13 | 45.0 | 39.0 | 15 | 30.0 | | 0.30 |
| HM3B14 | | 14 | 48.0 | 42.0 | 15 | 32.0 | | 0.35 |
| HM3B15 | | 15 | 51.0 | 45.0 | 15 | 36.0 | | 0.40 |
| HM3B16 | | 16 | 54.0 | 48.0 | 15 | 38.0 | | 0.50 |
| HM3B17 | | 17 | 57.0 | 51.0 | 15 | 39.0 | | 0.65 |
| HM3B18 | | 18 | 60.0 | 54.0 | 15 | 40.0 | | 0.67 |
| HM3B19 | | 19 | 63.0 | 57.0 | 15 | 45.0 | | 0.73 |
| HM3B20 | | 20 | 66.0 | 60.0 | 15 | 50.0 | | 0.80 |
| HM3B21 | | 21 | 69.0 | 63.0 | 15 | 52.0 | | 1.00 |
| HM3B22 | | 22 | 72.0 | 66.0 | 15 | 54.0 | | 1.10 |
| HM3B23 | | 23 | 75.0 | 69.0 | 15 | 56.0 | | 1.10 |
| HM3B24 | | 24 | 78.0 | 72.0 | 15 | 58.0 | | 1.20 |
| HM3B25 | | 25 | 81.0 | 75.0 | 20 | 60.0 | | 1.30 |
| HM3B26 | | 26 | 84.0 | 78.0 | 20 | 65.0 | | 1.50 |
| HM3B27 | | 27 | 87.0 | 81.0 | 20 | 65.0 | | 1.60 |
| HM3B28 | | 28 | 90.0 | 84.0 | 20 | 70.0 | | 1.70 |
| HM3B29 | | 29 | 93.0 | 87.0 | 20 | 70.0 | | 1.70 |
| HM3B30 | | 30 | 96.0 | 90.0 | 20 | 75.0 | | 1.80 |
| HM3B32 | | 32 | 102.0 | 96.0 | 20 | 75.0 | | 2.10 |
| HM3B34 | 34 | 108.0 | 102.0 | 20 | 80.0 | 2.40 | | |
| HM3B35 | 35 | 111.0 | 105.0 | 20 | 80.0 | 2.50 | | |
| HM3B36 | 36 | 114.0 | 108.0 | 20 | 80.0 | 2.60 | | |
| HM3B38 | 38 | 120.0 | 114.0 | 25 | 80.0 | 3.00 | | |
| HM3B40 | 40 | 126.0 | 120.0 | 25 | 80.0 | 3.10 | | |

●材質は機械構造用炭素鋼です。



ご注文の際は形式でご用命ください。


●平歯車のご注文表記例

HM 4 B 12
形式

(単位:mm)

| 形式 | 歯幅 t | 歯数 T | 歯先円直径 Do | 基準円直径 Dp | 軸穴径 d | ボス径 BD | 全長 BL | 概略重量 kg |
|--------|---------|---------|-------------|-------------|----------|-----------|----------|------------|
| HM4B12 | 40 | 12 | 56.0 | 48.0 | 20 | 35.0 | 60 | 0.55 |
| HM4B13 | | 13 | 60.0 | 52.0 | 20 | 38.0 | | 0.67 |
| HM4B14 | | 14 | 64.0 | 56.0 | 20 | 40.0 | | 0.80 |
| HM4B15 | | 15 | 68.0 | 60.0 | 20 | 45.0 | | 0.95 |
| HM4B16 | | 16 | 72.0 | 64.0 | 20 | 50.0 | | 1.10 |
| HM4B17 | | 17 | 76.0 | 68.0 | 20 | 53.0 | | 1.30 |
| HM4B18 | | 18 | 80.0 | 72.0 | 20 | 55.0 | | 1.50 |
| HM4B19 | | 19 | 84.0 | 76.0 | 20 | 60.0 | | 1.70 |
| HM4B20 | | 20 | 88.0 | 80.0 | 20 | 65.0 | | 1.90 |
| HM4B21 | | 21 | 92.0 | 84.0 | 20 | 69.0 | | 2.20 |
| HM4B22 | | 22 | 96.0 | 88.0 | 20 | 73.0 | 2.40 | |
| HM4B23 | | 23 | 100.0 | 92.0 | 20 | 77.0 | 2.60 | |
| HM4B24 | | 24 | 104.0 | 96.0 | 20 | 80.0 | 2.90 | |
| HM4B25 | | 25 | 108.0 | 100.0 | 20 | 84.0 | 3.20 | |
| HM4B26 | | 26 | 112.0 | 104.0 | 20 | 87.0 | 3.50 | |
| HM4B27 | | 27 | 116.0 | 108.0 | 20 | 90.0 | 3.80 | |
| HM4B28 | | 28 | 120.0 | 112.0 | 20 | 95.0 | 4.20 | |
| HM4B29 | | 29 | 124.0 | 116.0 | 20 | 95.0 | 4.40 | |
| HM4B30 | | 30 | 128.0 | 120.0 | 20 | 100.0 | 4.50 | |
| HM4B32 | | 32 | 136.0 | 128.0 | 22 | 100.0 | 56 | 4.80 |
| HM4B34 | 34 | 144.0 | 136.0 | 22 | 100.0 | 5.50 | | |
| HM4B35 | 35 | 148.0 | 140.0 | 22 | 100.0 | 5.60 | | |
| HM4B36 | 36 | 152.0 | 144.0 | 22 | 100.0 | 5.70 | | |
| HM4B38 | 38 | 160.0 | 152.0 | 22 | 100.0 | 7.10 | | |
| HM4B40 | 40 | 168.0 | 160.0 | 25 | 100.0 | 7.20 | | |

●材質は機械構造用炭素鋼です。



ご注文の際は形式でご用命ください。


●平歯車のご注文表記例

HM 5 B 12
形式

(単位:mm)

| 形式 | 歯幅 t | 歯数 T | 歯先円直径 Do | 基準円直径 Dp | 軸穴径 d | ボス径 BD | 全長 BL | 概略重量 kg |
|--------|---------|---------|-------------|-------------|----------|-----------|----------|------------|
| HM5B12 | 50 | 12 | 70.0 | 60.0 | 22 | 46.0 | 75 | 1.2 |
| HM5B13 | | 13 | 75.0 | 65.0 | 22 | 50.0 | | 1.5 |
| HM5B14 | | 14 | 80.0 | 70.0 | 22 | 52.0 | | 1.7 |
| HM5B15 | | 15 | 85.0 | 75.0 | 22 | 60.0 | | 2.0 |
| HM5B16 | | 16 | 90.0 | 80.0 | 22 | 65.0 | | 2.3 |
| HM5B17 | | 17 | 95.0 | 85.0 | 22 | 68.0 | | 2.6 |
| HM5B18 | | 18 | 100.0 | 90.0 | 22 | 70.0 | | 2.9 |
| HM5B19 | | 19 | 105.0 | 95.0 | 22 | 76.0 | | 3.5 |
| HM5B20 | | 20 | 110.0 | 100.0 | 22 | 82.0 | | 3.8 |
| HM5B21 | | 21 | 115.0 | 105.0 | 25 | 90.0 | | 4.4 |
| HM5B22 | | 22 | 120.0 | 110.0 | 25 | 95.0 | 4.8 | |
| HM5B23 | | 23 | 125.0 | 115.0 | 25 | 100.0 | 5.5 | |
| HM5B24 | | 24 | 130.0 | 120.0 | 25 | 100.0 | 5.7 | |
| HM5B25 | | 25 | 135.0 | 125.0 | 25 | 105.0 | 6.4 | |
| HM5B26 | | 26 | 140.0 | 130.0 | 25 | 110.0 | 6.6 | |
| HM5B27 | | 27 | 145.0 | 135.0 | 25 | 110.0 | 7.6 | |
| HM5B28 | | 28 | 150.0 | 140.0 | 25 | 110.0 | 8.0 | |
| HM5B29 | | 29 | 155.0 | 145.0 | 25 | 115.0 | 8.2 | |
| HM5B30 | | 30 | 160.0 | 150.0 | 25 | 120.0 | 8.8 | |
| HM5B32 | | 32 | 170.0 | 160.0 | 30 | 120.0 | 71 | 9.8 |
| HM5B34 | 34 | 180.0 | 170.0 | 30 | 120.0 | 11.8 | | |
| HM5B35 | 35 | 185.0 | 175.0 | 30 | 120.0 | 12.0 | | |
| HM5B36 | 36 | 190.0 | 180.0 | 30 | 120.0 | 12.0 | | |
| HM5B38 | 38 | 200.0 | 190.0 | 30 | 120.0 | 14.0 | | |
| HM5B40 | 40 | 210.0 | 200.0 | 30 | 120.0 | 13.0 | | |

●材質は機械構造用炭素鋼です。



ご注文の際は形式でご用命ください。

●平歯車のご注文表記例

HM 6 B 12
形式

(単位:mm)

| 形式 | 歯幅 t | 歯数 T | 歯先円直径 Do | 基準円直径 Dp | 軸穴径 d | ボス径 BD | 全長 BL | 概略重量 kg |
|--------|---------|---------|-------------|-------------|----------|-----------|----------|------------|
| HM6B12 | 60 | 12 | 84.0 | 72.0 | 25 | 55.0 | 88 | 2.0 |
| HM6B13 | | 13 | 90.0 | 78.0 | 25 | 58.0 | | 2.5 |
| HM6B14 | | 14 | 96.0 | 84.0 | 25 | 60.0 | | 2.8 |
| HM6B15 | | 15 | 102.0 | 90.0 | 25 | 70.0 | | 3.4 |
| HM6B16 | | 16 | 108.0 | 96.0 | 25 | 75.0 | | 3.9 |
| HM6B17 | | 17 | 114.0 | 102.0 | 25 | 78.0 | | 4.4 |
| HM6B18 | | 18 | 120.0 | 108.0 | 25 | 80.0 | | 5.0 |
| HM6B19 | | 19 | 126.0 | 114.0 | 25 | 90.0 | | 5.8 |
| HM6B20 | | 20 | 132.0 | 120.0 | 25 | 100.0 | | 6.5 |
| HM6B21 | | 21 | 138.0 | 126.0 | 28 | 105.0 | | 7.5 |
| HM6B22 | | 22 | 144.0 | 132.0 | 28 | 110.0 | | 8.1 |
| HM6B23 | | 23 | 150.0 | 138.0 | 28 | 115.0 | | 8.9 |
| HM6B24 | | 24 | 156.0 | 144.0 | 28 | 120.0 | 9.8 | |
| HM6B25 | | 25 | 162.0 | 150.0 | 28 | 125.0 | 10.5 | |
| HM6B26 | | 26 | 168.0 | 156.0 | 28 | 130.0 | 11.4 | |
| HM6B27 | | 27 | 174.0 | 162.0 | 28 | 135.0 | 12.1 | |
| HM6B28 | | 28 | 180.0 | 168.0 | 28 | 140.0 | 12.7 | |
| HM6B30 | | 30 | 192.0 | 180.0 | 30 | 150.0 | 15.1 | |
| HM6B32 | | 32 | 204.0 | 192.0 | 30 | 150.0 | 18.0 | |
| HM6B34 | | 34 | 216.0 | 204.0 | 30 | 150.0 | 19.0 | |
| HM6B35 | 35 | 222.0 | 210.0 | 30 | 150.0 | 19.0 | | |
| HM6B36 | 36 | 228.0 | 216.0 | 30 | 150.0 | 22.0 | | |
| HM6B38 | 38 | 240.0 | 228.0 | 30 | 150.0 | 23.0 | | |
| HM6B40 | 40 | 252.0 | 240.0 | 30 | 150.0 | 24.0 | | |

●材質は機械構造用炭素鋼です。